

MATERIAL SAFETY DATA SHEET (MSDS)

PRODUCT IDENTITY *(as indicated on label)*
BOOST IT

PRODUCT CODE
TR

Section 1 Company Identification

| | |
|---|---|
| Distributor's Name jRocco Hair Care | Emergency Telephone Number (908) 507-5300 |
| Address <i>(Number, Street, City, State, and ZIP Code)</i> 1705 ROSEMARY DRIVE | Telephone Number International (Collect Calls Accepted) (908) 507-2782 |
| CASTLE ROCK, CO 80109 | Date Prepared 1/28/2011 |

Section 2 Hazardous Ingredients/Identity Information

| Hazardous Components [Specific Chemical Identity; Common Name(s)] | CAS Number | Vapor Pressure | OSHA PEL | ACGIH TLV |
|--|------------|-----------------|----------|-----------|
| Hydrofluorocarbon 152a ≤18% | 75-37-6 | 62.5 psig @70°F | 1000 | 1000 |
| Dimethyl Ether (DME) ≤3% | 115-10-6 | 62 psig@70°F | 1000 | 1000 |
| Butane ≤3% | 106-97-8 | 17 psig @70°F | 1000 | 1000 |

N/E = not established for this material

Section 3 Hazards Identification

EMERGENCY OVERVIEW Type of Hazard: Inhalation (S2,S15,S16,S47, R5,R44)

POTENTIAL HEALTH EFFECTS

Inhalation: Intentional inhalation of vapors can cause nasal and respiratory irritation: dizziness, weakness, nausea, headache, possible unconsciousness and even asphyxiation (S23,S51,R20,R39)

Skin Contact: Practically non-irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dryness. Skin Absorption: none to Slight (R38)

Eye Contact: May cause mild to severe eye irritation (S25,R36)

Ingestion: Acute discomfort, cramping,diarrhea. No chronic effectsare expected from a single accidental ingestion.. (R22)

Chronic Effects and Medical Conditions Aggravated By Overexposure: None when used as directed

Section 4 First Aid Measures

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. Get medical attention. (S45, S63)

SKIN: Thoroughly wash exposed area. If irritation persists, seek medical attention (S28, S45)

EYES: Flush with copious amounts of water for 15 minutes. If irritation persists, seek medical attention S26,S45)

INGESTION: DO NOT induce vomiting. Get medical attention IMMEDIATELY.(S45,S62, S64)

Section 5 Fire Fighting Measures

MATERIAL SAFETY DATA SHEET (MSDS)

FLAMMABILITY CLASSIFICATION: **Non Flammable** pursuant to
CFR16 Ch11 Subchapter C, part 1500.45

FLASH POINT: N/E

UNUSUAL FIRE AND EXPLOSION HAZARDS: Aerosols will burst at temperatures above 130°F (55°C). containers exposed to intense heat from fires must be cooled with water to prevent vapor pressure build up which could result in container rupture (S47,R5,R7)

SPECIAL FIRE FIGHTING PROCEDURES: Use Self-contained breathing apparatus. Water may be used on containers exposed to intense heat to prevent vapor pressure build up and container rupture. Keep containers cooled with water and remove them from danger as soon as possible. If aerosols are bursting, stay clear until bursting is completed. Aerosols can be projectiles when bursting. (S43)

NFPA 30B Storage Classification of Aerosol: Level 1

PRODUCT IDENTITY (as indicated on label)

Texture Rising 6% VOC

PRODUCT CODE

Section 6 Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep sources of ignition and hot metals isolated from the spill. Small leaks can be mopped or wiped up immediately. Remove material to out of doors. Large leaks should be handled as follows: Evacuate area. Contain liquid; transfer to closed containers. Keep out of water supplies. (S16,S29,S36,S38,S56,S57,R5)

DISPOSAL METHOD: dispose of according to federal, state and locals regulations. Disposal should be carried out under EPA state and federal laws

Section 7 Handling and Storage

USAGE PRECAUTIONS: Contents under pressure. Do not puncture or burn even after use. Keep away from heat, sparks, or flame. Extinguish pilot lights, cigarettes or other sources of ignition. Use with adequate ventilation. (S15,S16,S39,S40,S59)

STORAGE PRECAUTIONS: Keep containers cool in temperatures below 120°F. Keep containers dry, closed and upright when not in use. (S3,S8, S9,S15,S18,S53)

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. Avoid contact with eyes. Maintain personal hygiene and good housekeeping .

Section 8 Exposure Controls and Personal Protection

RESPIRATION CONTROL: If used with adequate ventilation, no protective equipment is necessary. In enclosed spaces if exposure limits are exceeded use a NIOSH approved cartridge respirator.(S38)

VENTILATION: A well ventilated room with adequate air circulation. (S90,S51)

PROTECTIVE GLOVES: Wear chemical resistant gloves and other clothing as required to minimize prolonged or repeated contact with skin.(S36)

EYE AND FACE PROTECTION: Chemical goggles if likelihood of eye contact (S36,S39)

HYGENIC WORK PRACTICES: Wash well with soap and water after use of product.

Section 9 Physical and Chemical Properties

BOILING RANGE: N/A

VAPOR PRESSURE: 72-82 psig @ 70°F

MATERIAL SAFETY DATA SHEET (MSDS)

| | | |
|---|--|---|
| PERCENT VOLATILE PER VOLUME: 6% | | EVAPORATION RATE(concentrate): (n-Butyl Acetate = 1) Greater than 1 |
| pH: 5.5 -6.0 (conc only) | WEIGHT PER GALLON: 8.5 (concentrate only) | SPECIFIC GRAVITY: 1.02 (H ₂ O=1) (concentrate only) |
| SOLUBILITY IN WATER: Moderately Soluble | | VISCOSITY: 2,500 – 3,500 cps (Conc) Sp # 4 @ 10 rpm |

APPEARANCE: White, foamy consistency
ODOR: Characteristic

MATERIAL SAFETY DATA SHEET (MSDS)

PRODUCT IDENTITY (as indicated on label)

Texture Rising 6% VOC

PRODUCT CODE

Section 10 Stability and Reactivity

STABILITY Unstable
 Stable

HAZARDOUS POLYMERIZATION May Occur
 Will Not Occur

INCOMPATIBILITY (*Materials to Avoid*) Strong oxidizing agents, strong acids and bases (S14,S50)

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide and other unidentified organic compounds may be formed during combustion.

CONDITIONS TO AVOID: High temperatures above 120°F, Open flames, sparks (S47)

Section 11 Toxicological Information

No definite information available on carcinogenicity, mutagenicity, target organs or developmental toxicity.

Section 12 Ecological Information

Product is in recyclable aluminum container

Section 13 Disposal Considerations

Dispose in accordance with federal, state and local regulations. Disposal should be carried out under EPA state and federal laws. (S35,S56.S60)

Section 14 Transport Information

1. **DOT:** Shipping name – Consumer Commodity Hazard Class – ORM-D
2. **IMGD** (by water overseas) Shipping name: Aerosols Class: 2 UN No.: 1950 Label: None
IMGD code: Page 2102
3. **IATA** (by air) Shipping name: Consumer Commodity Class: 9 ID No.: 8000 (Export) / ORM-D
AIR (Domestic)
Label Domestic: Consumer Commodity ORM-D Air. Label Export: Aerosol Flammable

Section 15 Regulatory Information

SARA Hazard Category: This material has been reviewed according to the EPA Hazard Categories promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered to meet the following categories: NONE

SARA, Title III, Section 313 (40CFR 372): There are no Chemicals subject to reporting in Section 313 of Title III.

California Proposition 65: The following statement is made in compliance with the California Safe Drinking and Toxic Enforcement Act of 1988: This material does not contain any chemicals known to the State of California to cause cancer

Section 16 Other Information

MATERIAL SAFETY DATA SHEET (MSDS)

HAZARD RATING: Flammable 210 Aerosol level 1

REVISION DATE: 1/28/11
